NATIONAL INSTITUTE OF TECHNOLOGY KARNATAKA, SURATHKAL

DEPARTMENT OF OFFICE OF THE RESIDENT ENGINEER POST SRINIVASNAGAR, MANGALURU - 575025 (DK)

Phone: [0824] 2474000 E - mail: info@nitk.ac.in

Fax: [0824] 2474033 Website: http://www.nitk.ac.in



NOTICE INVITING QUOTATIONS

: Store/EI-SQ-01/2018-19/SK, Date: 27-09-2018 Notification

: Electrical materials Name of goods

Estimate Amount : Rs. 1, 70,000.00

EMD Amount : NIL

Time for supply of items

: Seven Days After release of Purchase order

: 12-10-2018 before 3.30 PM Last date for submission of Quotation

: Office of the Resident Engineer, Address for submission of Quotation

Post Srinivasnagar, Surathkal,

Mangaluru - 575025 [DK]

: 27.10.2018 at 4.00 PM [if possible] Date of opening of Quotation

> nt Engineer amonal Institute of Technology Karnataka urathkal. P.O. Srinivasnagar - 575 025. D.K

OFFICE OF THE RESIDENT ENGINEER NATIONALINSTITUTE OF TECHNOLOGY KARNATAKA, SURATHKAL Srinivasnagar Post: 575 025 - MANGALURU - D.K.



Extn: 3028 & 3031 Fax: (0824) 2474000-023 No. Stores/El-SQ-1/2018-19/SK

Date: 27/09/2018

NOTICE INVITING QUOTATIONS

The National Institute of Technology Karnataka, Surathkal (in short - NITK, Surathkal or Institute) is an autonomous Institute of the Govt. of India [under the Ministry of HRD] imparting technical and science education. The Institute intends to purchase the materials as listed in the sheet enclosed. In this connection, sealed quotations are invited by the undersigned subject to the terms and conditions enumerated hereunder from the manufacturers/ authorized dealers/ agencies so as to reach this office on or before 12-10-2018 by 3:30 PM. The quotations shall oe opened on the same day if possible.

Terms and conditions:

1. The intending bidder shall quote his rates in the 'Quotation Format' enclosed hear with either in his letter head or using the same format. He shall sign each page with seal of the firm. Envelope super scripted as "Quotation for the supplying 4'-20W LED batten fittings & 12W circular type and square type surface mounted LED downlight fittings; Due on 12-10-2018" and addressed to as "The Resident Engineer, NITK, Surathkal, Post Srinivasnagar, Mangaluru - 575025" be sent so as to reach this office on or before the due date mentioned.

2. The GST registration number and the PAN number of the bidder shall be mentioned in the quotation. Quotation without these information will not be accepted.

3. Quotation may be dropped in the Tender Box kept in the office or may be sent by post/ courier. It is the responsibility of the bidder to make sure that the quotation is delivered in time. The quotations received after the due date will not be entertained.

4. The bidder shall specify the make of material for which the rate is offered by him. The bidder may quote for

5. The bidder shall mention the Warranty period of the material for which the rate is offered by him (if

6. GST rate as applicable shall be mentioned clearly

7. Freight of Rate [F.O.R] - Store Section at Resident Engineer's office, NITK, Surathkal.

8. The rate quoted shall be valid for 90 days for its acceptance.

- 9. The quotation/ bid shall be accepted as a whole or parts thereof depending on the lowest rate quoted for individual items. The bidder shall supply the materials accordingly.
- 10. The material (s) should be supplied within 7 days from the date of confirmation of acceptance of the
- 11. The material supplied should be strictly as per the specification specified, without which the material will
- 12. In case of rejection of material, one more chance shall be given for its replacement with the material conforming to the specification specified. Failure to supply the material as per the specification will result in debarring the bidder for participation in bids for a minimum of one year.

13. The right of selection of any brand of material irrespective of lowest rate is reserved.

- 14. No advance payment will be made. The payment shall be made within 30 days from the date of supply of material along with the bill. No interest will be paid for delayed payments if any.
- 15. The rate quoted should be firm. No claim for enhancement of rate is admissible after opening of the
- 16. The Institute reserves the rights to cancel the quotations accept any quotation other than the lowest or modify the quantity of the goods at any time after/ before opening of the quotation. The bidder shall have no

17. Terms and conditions stipulated in this Notice inviting conditions are binding on the bidder. Quotations with conditions in contrary to this NIQ are liable for rejection.

Resident Engineer NITK, Surathkal Resident Engineer National has state of Techporot, Karnataka Buratinkal, P.O. Gripivasnagar, 575 025 L.K. Name and Address of the Bidder:

GST registration number:-PAN number:-

Date: - 27-09-2018

QUOTATION

То

The Resident Engineer, Office of the Resident Engineer, N.I.T.K., Surathkal.

	Sl. No	Description of the items	Quantity	Rate	GST	Amount Rs.
Al. extrusion. Front Cover: Diffused PS/PMMA. LED: LM80 certified LED Gear: Electronic constant current driver. Internal Wiring: Teflon insulated, Cu. Conductor. Hardware: Ms zinc plated & passivated. Ingress protection: IP20 Lumen maintenance: 50,000 Hrs @ L70 Operating temperature: -10 C to 50 C Rated voltage & frequency: 240V, 50Hz AC Current: <0.09A P.F: > 0.95 Efficacy: >= 100 lm/W CCT: 5700K-6500K Luminare manufacturer should have in house facility accredited by NABL/CPRI & any govt certified agency & design & developmant facillity certified by ISO 9001:2008. Warranty: Min two year Protections: Open & Short circuit protection, high and low voltage cut off and surge protection 3KV. Make: Phillips / CG / Havells / Bajaj /	01	fittings with following specification: Wattage: 20W +/- 10%	200 nos.			
LED: LM80 certified LED Gear: Electronic constant current driver. Internal Wiring: Teflon insulated, Cu. Conductor. Hardware: Ms zinc plated & passivated. Ingress protection: IP20 Lumen maintenance: 50,000 Hrs @ L70 Operating temperature: -10 C to 50 C Rated voltage & frequency: 240V, 50Hz AC Current: <0.09A P.F:>0.95 Efficacy: >= 100 lm/W CCT: 5700K-6500K Luminare manufacturer should have in house facility accredited by NABL/CPRI & any govt certified agency & design & developmant facillity certified by ISO 9001:2008. Warranty: Min two year Protections: Open & Short circuit protection, high and low voltage cut off and surge protection 3KV.						
driver. Internal Wiring: Teflon insulated, Cu. Conductor. Hardware: Ms zinc plated & passivated. Ingress protection: IP20 Lumen maintenance: 50,000 Hrs @ L70 Operating temperature: -10□C to 50□C Rated voltage & frequency: 240V, 50Hz AC Current: <0.09A P.F: > 0.95 Efficacy: >= 100 lm/W CCT: 5700K-6500K Luminare manufacturer should have in house facility accredited by NABL/CPRI & any govt certified agency & design & developmant facillity certified by ISO 9001:2008. Warranty: Min two year Protections: Open & Short circuit protection, high and low voltage cut off and surge protection 3KV. Make: Phillips / CG / Havells / Bajaj /		LED: LM80 certified LED		Na.		
Hardware: Ms zinc plated & passivated. Ingress protection: IP20 Lumen maintenance: 50,000 Hrs @ L70 Operating temperature: -10□C to 50□C Rated voltage & frequency: 240V, 50Hz AC Current: <0.09A P.F: > 0.95 Efficacy: >= 100 lm/W CCT: 5700K-6500K Luminare manufacturer should have in house facility accredited by NABL/CPRI & any govt certified agency & design & developmant facility certified by ISO 9001:2008. Warranty: Min two year Protections: Open & Short circuit protection, high and low voltage cut off and surge protection 3KV. Make: Phillips / CG / Havells / Bajaj /		driver. Internal Wiring: Teflon				
Ingress protection: IP20 Lumen maintenance: 50,000 Hrs @ L70 Operating temperature: -10 C to 50 C Rated voltage & frequency: 240V, 50Hz AC Current: <0.09A P.F: > 0.95 Efficacy: >= 100 lm/W CCT: 5700K-6500K Luminare manufacturer should have in house facility accredited by NABL/CPRI & any govt certified agency & design & developmant facillity certified by ISO 9001:2008. Warranty: Min two year Protections: Open & Short circuit protection, high and low voltage cut off and surge protection 3KV. Make: Phillips / CG / Havells / Bajaj /		Hardware: Ms zinc plated &				
L70 Operating temperature: -10 C to 50 C Rated voltage & frequency: 240V, 50Hz AC Current: <0.09A P.F: > 0.95 Efficacy: >= 100 lm/W CCT: 5700K-6500K Luminare manufacturer should have in house facility accredited by NABL/CPRI & any govt certified agency & design & developmant facillity certified by ISO 9001:2008. Warranty: Min two year Protections: Open & Short circuit protection, high and low voltage cut off and surge protection 3KV. Make: Phillips / CG / Havells / Bajaj /		Ingress protection: IP20	×			
Rated voltage & frequency: 240V, 50Hz AC Current: <0.09A P.F: > 0.95 Efficacy: >= 100 lm/W CCT: 5700K-6500K Luminare manufacturer should have in house facility accredited by NABL/CPRI & any govt certified agency & design & developmant facillity certified by ISO 9001:2008. Warranty: Min two year Protections: Open & Short circuit protection, high and low voltage cut off and surge protection 3KV. Make: Phillips / CG / Havells / Bajaj /		L70 Operating temperature: -10 C to				
P.F: > 0.95 Efficacy: >= 100 lm/W CCT: 5700K-6500K Luminare manufacturer should have in house facility accredited by NABL/CPRI & any govt certified agency & design & development facillity certified by ISO 9001:2008. Warranty: Min two year Protections: Open & Short circuit protection, high and low voltage cut off and surge protection 3KV. Make: Phillips / CG / Havells / Bajaj /		Rated voltage & frequency: 240V, 50Hz AC				
CCT: 5700K-6500K Luminare manufacturer should have in house facility accredited by NABL/CPRI & any govt certified agency & design & development facillity certified by ISO 9001:2008. Warranty: Min two year Protections: Open & Short circuit protection, high and low voltage cut off and surge protection 3KV. Make: Phillips / CG / Havells / Bajaj /		P.F: > 0.95				
house facility accredited by NABL/CPRI & any govt certified agency & design & development facillity certified by ISO 9001:2008. Warranty: Min two year Protections: Open & Short circuit protection, high and low voltage cut off and surge protection 3KV. Make: Phillips / CG / Havells / Bajaj /		CCT: 5700K-6500K	Silvania I	ie:		
agency & design & development facillity certified by ISO 9001:2008. Warranty: Min two year Protections: Open & Short circuit protection, high and low voltage cut off and surge protection 3KV. Make: Phillips / CG / Havells / Bajaj /		house facility accredited by				
Protections: Open & Short circuit protection, high and low voltage cut off and surge protection 3KV. Make: Phillips / CG / Havells / Bajaj /		agency & design & development facility certified by ISO 9001:2008.	*			
and surge protection 3KV. Make: Phillips / CG / Havells / Bajaj /		Protections: Open & Short circuit	*			
						*
			- 4			

16		
02	Supplying 12W circular surface mounted LED downlight fittings with following specification: Wattage: 12W +/- 10% Main Housing, frame: Powder coated, PDC Al. housing Front Cover: Diffused polycarbonate cover. LED: LM80 certified LED Gear: Electronic constant current driver. Internal Wiring: Teflon insulated, Cu. Conductor. Hardware: Ms zinc plated & passivated. Ingress protection: IP20 Lumen maintenance: 50,000 Hrs @ L70 Operating temperature: -10 C to 50 C Rated voltage & frequency: 240V, 50Hz AC Current: <0.057A P.F:>0.95 Efficacy:>= 100 lm/W CCT: 5700K-6500K CRI: >80 Luminare manufacturer should have in house facility accredited by NABL/CPRI & any govt certified agency & design & developmant facillity certified by ISO 9001:2008. Warranty: Min two year Protections: Open & Short circuit protection, high and low voltage cut off and surge protection. Make: Phillips / CG / Havells / Bajaj / Wipro / Surya / Osram / Syska	50 nos
03	Supplying 12W square type surface mounted LED downlight fittings with following specification: Wattage: 12W +/- 10% Main Housing, frame: Powder coated, PDC Al. housing Front Cover: Diffused polycarbonate cover. LED: LM80 certified LED Gear: Electronic constant current driver. Internal Wiring: Teflon insulated, Cu. Conductor. Hardware: Ms zinc plated &	50 nos

1		
	passivated.	
	Ingress protection: IP20	
	Lumen maintenance: 50,000 Hrs @	
	L70	
	Operating temperature: -10□C to	
	50□C	
	Rated voltage & frequency: 240V,	
	50Hz AC	
	Current : <0.057A	
	P.F: > 0.95	
	Efficacy: >= 100 lm/W	
	CCT: 5700K-6500K	
	CRI: >80	
	Luminare manufacturer should have	
	in house facility accredited by NABL/CPRI & any govt certified	
	agency & design & development	
	facility certified by ISO 9001:2008.	
	Warranty: Min two year	
	Protections: Open & Short circuit	
	protection, high and low voltage cut	
	off and surge protection.	
	Make: Phillips / CG / Havells /	
	Bajaj / Wipro / Surya / Osram /	
	Syska	

Intelled billion like

(9)